

OT 2 PS



Control unit for sauna heaters 4.5-9 kW

OT 2 PS

Control units are equipped with a timer, thermostat, light switch and indicator light.

Measurements:

mm)

W

Pintamalli

Control unit	Surface model			
	W	Н	D	
ОТ	250	220	80	

Controlunit	OT 2 PS	Sauna heater type	
Assembly	surface	Softhot 45-90 D	
Classification	IP X4		
Voltage	400V 3N~		
Timer	0 - 8 h pre-set		
	0 - 4 h heating time		
Thermostat	OLET 6 - 1 with re-settable temperature limit switch		
	included in the delivery		

CE, FI





Electrical connections

NOTE: Always follow local regulations

	Cables mm ²					nin.)		
Sauna heater	Power kW	Fuse A	From the main panel to the control unit of the heater	From the control unit to the junction box	From the junction box to the heater	For the thermostat 3 m is included in the delivery		
Softhot 45 D	4,5	10	5 x 1,5 S	5 x 1,5 S	5 x 1,5 S	4 x 0,25		
Softhot 60 D	6,0	10	5 x 1,5 S	5 x 1,5 S	5 x 1,5 S	4 x 0,25		
Softhot 80 D	8,0	16	5 x 2,5 S	5 x 2,5 S	5 x 1,5 S	4 x 0,25		
Softhot 90 D	9,0	16	5 x 2,5 S	5 x 2,5 S	5 x 1,5 S	4 x 0,25		

OT 2 PS





- Supply
 Sauna heater
 Sauna light
 Electrical heating control
 Thermostat

Optional equipment Locking cover SY-ZZL 12





